

# Flange mounted range

MOTOR TYPE	FORCE NEWTONS	RATED OUTPUT		MOTOR MASS KG	DIMENSIONS IN MILLIMETRES												
		WATTS	AMP		A	B	C	D	E	F	G	H	J	K	L	M	

## 2 POLE (2880 RPM) 415V 3PH 50HZ

RF 42A	15000	500	1.3	45	400	280	200	220	16	10	220	4	12	254	113	75
RF 42B	20000	1120	2.6	75	480	315	240	260	20	12	240	6	20	275	130	75
RF 42C	25000	1600	3.5	91	525	315	240	285	20	12	240	6	20	275	147	90
RF 42CX	25000	1600	3.5	111	525	420	260	285	25	20	300	8	20	360	147	90
RF 42D	30000	2200	4.9	150	620	420	280	332	25	20	300	8	20	360	160	90
RF 42DX	30000	2200	4.9	165	620	510	280	332	25	20	360	8	24	438	160	90
RF 42E	40000	3000	6.5	208	690	510	330	367	27	20	360	8	24	438	185	100
RF 42F	50000	3750	8	227	740	510	330	392	27	20	360	8	24	438	185	100
RF 42G	60000	4500	9.5	239	760	510	330	402	27	20	360	8	24	438	185	100

## 4 POLE (1440RPM) 415V 3PH 50HZ

RF 44A	10000	450	1.3	50	400	280	200	220	16	10	220	4	12	254	113	75
RF 44B	15000	750	2.1	84	580	315	240	260	20	12	240	6	20	275	130	75
RF 44C	25000	1120	2.7	104	525	315	240	285	20	12	240	6	20	275	147	90
RF 44CX	25000	1600	2.7	124	525	420	260	285	25	20	300	8	20	360	147	90
RF 44D	35000	1600	3.8	167	620	420	280	332	25	20	300	8	20	360	160	90
RF 44DX	35000	1600	3.8	182	620	510	280	332	25	20	360	8	24	438	160	90
RF 44E	45000	2600	5.5	229	690	510	330	367	27	20	360	8	24	438	185	100
RF 44F	55000	3500	7.8	253	740	510	330	392	27	20	360	8	24	438	185	100
RF 44G	70000	4500	10.3	265	760	510	330	402	27	20	360	8	24	438	185	100
RF 44H	80000	6000	13.5	339	810	510	330	427	27	20	360	8	24	438	185	100
RF 44HX	80000	6000	13.5	360	810	590	370	427	27	20	445	8	24	495	185	100
RF 44J	100000	7500	16.1	452	1000	590	400	522	27	20	445	8	24	495	214	100
RF 44K	150000	9500	19	610	1050	590	430	547	27	20	445	8	24	495	235	100

## 6 POLE (960RPM) 415V 3PH 50HZ

RF 46A	5000	375	1.3	52	400	280	200	220	16	10	220	4	12	254	113	75
RF 46B	10000	560	1.8	89	480	315	240	260	20	12	240	6	20	275	130	75
RF 46CX	15000	750	2.1	130	525	420	260	285	25	20	300	8	20	360	147	90
RF 46D	25000	1120	3.1	179	620	420	280	332	25	20	300	8	20	360	160	90
RF 46DX	25000	1120	3.1	194	620	510	280	332	25	20	360	8	24	438	160	90
RF 46E	35000	2200	5.4	247	690	510	330	367	27	20	360	8	24	438	185	100
RF 46F	45000	2600	6.4	275	740	510	330	392	27	20	360	8	24	438	185	100
RF 46G	55000	3750	8.5	288	760	510	330	402	27	20	360	8	24	438	185	100
RF 46HX	70000	4100	9.5	389	810	590	370	427	27	20	445	8	24	495	185	100
RF 46J	100000	5500	12.9	472	1000	590	400	522	27	20	445	8	24	495	214	100
RF 46K	150000	7500	17.5	660	1050	590	430	547	27	20	445	8	24	495	235	100